

Technical Specifications

Duend	Howlett Deckard Fatoronics (UDF)
Brand	Hewlett-Packard Enterprise (HPE)
Country of Origin	U.S. A
Model	Aruba AP-515 WI-FI 6 Indoor Access Points
AP type	Indoor
	Dual radio, 5GHz 802.11ax 4x4 MIMO and 2.4 GHz 802.11ax 2x2 MIMO
	Support for up to 512 associated client devices per radio, and up to 16 BSSIDs per
	radio
	5GHz radio: Four spatial stream Multi User (MU) MIMO for up to 4.8Gbps
	wireless data rate to up to four 1SS or two 2SS HE160 802.11ax DL-MU-MIMO
	capable client devices simultaneously (max)
Wi-Fi radio	2.4GHz radio: Two spatial stream Single User (SU) MIMO for up to 574Mbps
specifications	wireless data rate to 2SS HE40 802.11ax client devices (max)
	802.11b: Direct-Sequence Spread-Spectrum (DSSS)
	Low-Density Parity Check (LDPC) for high-efficiency error correction and increased
	throughput
	802.11mc Fine Timing Measurement (FTM) for precision distance ranging
Supported radio	802.11ax Target Wait Time (TWT) to support low-power client devices
technologies:	Transmit Beam-Forming (TxBF) for increased signal reliability and range
	Four integrated dual-band downtilt omnidirectional antennas for 4x4 MIMO (2x2
	MIMO for 2.4GHz) with peak antenna gain of 4.2dBi in 2.4GHz and 7.5dBi in 5GHz.
	Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP.
	The downtilt angle for maximum gain is roughly 30 degrees
	Combining the patterns of each of the antennas of the MIMO radios, the peak gain of
Wi-Fi antennas	the effective per-antenna pattern is 3.8dBi in 2.4 GHz and 4.6dBi in 5 GHz
	Wi-Fi CERTIFIED a, b, g, n, ac, ax
	WPA, WPA2 and WPA3—Enterprise with CNSA option, Personal (SAE), Enhanced
	Open (OWE)
	WMM, WMM-PS, W-Fi Agile Multiband
	Bluetooth SIG
Certifications	Wi-Fi CERTIFIED Location™ and Passpoint (release 2)
	10/100/1000BASE-T Ethernet network interface (RJ-45)
	Auto-sensing link speed and MDI/MDX
	802.3az Energy Efficient Ethernet (EEE)
features	USB 2.0 host interface (Type A connector)
	The AP supports Power over Ethernet (PoE)
	Maximum (worst-case) power consumption in idle mode: 12.6W (POE) or 9.7W (DC)
	Maximum (worst-case) power consumption in deep-sleep mode: 5.9W (POE) or
Power sources	1.5W (DC)
1 OWCI SOUICES	11.000 (00)



Warranty	Limited Lifetime Warranty
Wi-Fi features	Low-Density Parity Check (LDPC)
	Space-Time Block Coding
	Cyclic Delay/Shift Diversity (CDD/CSD)
	Maximum Ratio Combining (MRC)
	Dynamic Frequency Selection (DFS)
	Passpoint Wi-Fi (Release 2) (Hotspot 2.0)
	Transmit Beamforming